

# TY GIUNTI ELASTICI A COPERTONE / TYRE ELASTIC COUPLINGS

Giunto standard: ghisa UNI EN 1561 EN-GJL-HB 175  
 Standard coupling: cast iron UNI EN 1561 EN-GJL-HB 175  
 Manicotto in gomma: Shore 75-80 temperatura di esercizio -20° +80°  
 Elastic tyre: Shore 75-80 operating temperature -20° +80°



TIPO TYPE	Mt torque [Nm]	[giri/min] [RPM] max	∅ grezzo/max. raw/max. [mm]	F [mm]	D [mm]	S [mm]	M [mm]	H [mm]	L [mm]	peso weight [Kg]
TY 100	40	4500	15 / 30	80	100	18	-	20	56	1,8
TY 130	60	4500	14 / 38	100	130	32	80	22	86	3
TY 160	120	4000	14 / 48	125	160	38	72	30	106	5
TY 190	240	3600	14 / 55	144	190	45	82	33	123	7,8
TY 210	350	3100	15 / 65	167	210	51	95	41	143	11
TY 230	490	2880	17 / 76	188	230	57	110	42,5	156,5	16,5
TY 250	670	2600	17 / 85	216	250	60	124	42	162	26
TY 275	865	2300	17 / 90	233	275	65	135	44	174	31
TY 310	1350	2050	21 / 102	264	310	76	152	47	199	45,5
TY 355	2315	1800	32 / 120	311	355	90	195	11,5	191,5	61
TY 395	3760	1600	32 / 140	345	395	102	216	8	212	86
TY 460	6260	1500	32 / 150	398	460	115	266	65	256	141

Da grandezza 100 a grandezza 310  
 From size 100 to size 310

Da grandezza 355 a grandezza 470  
 From size 355 to size 470

