

E/BM GIUNTI ELASTICI A PIOLI CON FLANGIA MINIMO INGOMBRO / PINS ELASTIC COUPLINGS WITH FLANGE AT MINIMUM SIZE

Giunto standard: ghisa UNI EN 1561 EN-GJL-HB 175
 Standard coupling: cast iron UNI EN 1561 EN-GJL-HB 175
 Flangia: acciaio UNI EN 10277-2-C45
 Flange: steel UNI EN 10277-2-C45
 Perni standard: acciaio zincato
 Standard pivot: galvanized steel
 Piolo in gomma: Shore 75-80 temperatura di esercizio -20° +80°
 Rubber pin: Shore 75-80 operating temperature -20° +80°
 A richiesta giunto completamente in C45 o INOX
 Coupling completely made of C45 or stainless steel upon request



TIPO TYPE	Mt torque [Nm]	Ø grezzo/max. raw/max. [mm]	Ø1 [mm]	F [mm]	F1 [mm]	L [mm]	H [mm]	K [mm]	K1 [mm]	M [mm]	S [mm]	N° perni Pivot	Ø perni Pivot
E120BM	350	- / 45	76	120	A richiesta Upon request	43	3	20	20	71	40	10	8
E140BM	600	- / 55	90	140		43	3	20	20	85	40	14	8
E160BM	900	- / 60	107	160		43	3	20	20	102	40	16	8
E180BM	1300	- / 65	111	180		54	4	25	25	103	50	12	12
E200BM	1800	- / 75	124	200		54	4	25	25	116	50	14	12
E225BM	2600	40 / 90	153	225		54	4	25	25	145	50	16	12
E250BM	4600	45 / 95	157	250		81	5	38	38	147	76	14	18
E300BM	6500	50 / 110	192	300		81	5	38	38	182	76	16	18
E350BM	10500	60 / 120	210	350		126	6	60	60	200	120	12	25
E400BM	14500	70 / 140	242	400		126	6	60	60	232	120	14	25
E450BM	21000	75 / 160	273	445		151	7	72	72	253	144	12	32
E500BM	28000	75 / 180	308	495		151	7	72	72	288	144	14	32
E550BM	36000	75 / 210	342	545		151	7	72	72	322	144	16	32
E630BM	75000	90 / 250	405	625		187	7	90	90	375	180	14	45
E680BM	95000	90 / 270	435	680		187	7	90	90	405	180	16	45
E800BM	146000	130 / 280	450	795		187	7	90	90	420	180	20	45
E900BM	200000	130 / 300	478	895		187	7	90	90	448	180	22	45
E1100BM	350000	130 / 350	580	1100		187	7	90	90	550	180	28	45

