

TE-S TRASMISSIONI ELASTICHE A PIOLI CON SUPPORTO / PINS ELASTIC TRANSMISSIONS WITH SUPPORT

Giunto standard: ghisa UNI EN 1561 EN-GJL-HB 175
 Standard coupling: cast iron UNI EN 1561 EN-GJL-HB 175
 Perni standard: acciaio zincato
 Standard pivot: galvanized steel
 Piolo in gomma: Shore 75-80 temperatura di esercizio -20° +80°
 Rubber pin: Shore 75-80 operating temperature -20° +80°
 Flange: acciaio UNI EN 10277-2-C45
 Flange steel: UNI EN 10277-2-C45
 Allunga centrale: acciaio UNI EN 10305-1-E235+A
 Central spacer steel: steel UNI EN 10305-1-E235+A
 A richiesta trasmissione completamente in C45 o INOX
 Coupling completely made of C45 or stainless steel upon request



TIPO TYPE	Mt torque [Nm]	∅ grezzo/max. raw/max. [mm]	F [mm]	H [mm]	K [mm]	M [mm]	S [mm]	N° perni corti short Pivot	N° perni lunghi long Pivot	∅ Perni Pivot
TE-S 160	900	- / 60	160	3	20	102	90	24	24	8XM8
TE-S 180	1300	- / 65	180	4	25	103	100	18	18	12XM12
TE-S 200	1800	- / 75	200	4	25	118	115	21	21	12XM12
TE-S 225	2600	40 / 90	225	4	25	145	130	24	24	12XM12
TE-S 250	4600	45 / 95	250	5	38	147	150	21	21	18XM18

* A RICHIESTA CLIENTE // UPON CLIENT'S REQUEST

